



Manu Data

Casement Window - Aluminum Clad

Frame:

- Pine, red grandis or mahogany
- Aluminum clad, extruded 0.060", 1.5 mm thick
- Thickness 1 ¼" (32mm)
- Depth 4 9/16" (116mm), or 6 9/16" (167mm)

Sash:

- Pine, red grandis or mahogany
- Aluminum clad, extruded 0.060", 1.5 mm thick
- Thickness 1 ¾" (44,5mm) or 2 ¼" (57mm)
- Colonial or contemporary

Interior finish:

- Natural, primed, first coat, Lepage stain or paint over 50 colors

Exterior finish:

- Lepage paint over 50 colors

Hardware:

- Truth, Encore series
- Retractable handle and stainless steel multipoint lock
- Colors available: white, beige, coppertone, black, oil rubbed bronze, polish brass, satin chrome, antique brass, satin nickel or polish chrome

Weather-strip

- Silicone, polyflex

Insulated glass:

- Double glaze ¾" (19 mm)
- Triple glaze 1 ¼" (32mm) with 2 ¼" (57mm) sash
- "Technoform" spacer, bronze, white, black or grey.
- Argon

Glass available:

- Clear, grey, bronze, pinhead, glue-chip
- Low-e: Energy advantage, 272, 366, 189
- Tempered
- Laminated

Screen:

- Mesh: invisible fiber glass, grey or black aluminium
- Surround: white, coppertone, beige, oil rubbed bronze or black
- Wood screen surround
- Retractable

Grilles:

- Removable 7/8"
- Internal georgian 3/4", 1" or 1 3/4"
- Internal flat 5/16", 5/8", 3/4" or 1"
- Internal tubular: white, brass or pewter

Simulated Divided Lites (SDL):

- 5/8", 7/8", 1 1/4" or 1 3/4"
- Spacer bars bronze, grey, white or black

True Divided Lites (TDL):

- TDL 1 3/4"

Casing:

- 908
- 2 3/4" Flat casing
- 3 1/2" Flat casing
- 3 15/16" Backbend (D-090)
- Nailing fin

Sill Extension:

- Standard D-082 (1" x 1 1/4")
- Historic D-083 (1 3/4" x 2")

Interior Jamb Extension:

- Finish and wood species same as interior frame 1/8" min and 6" max

1 3/4" Sash Window - Minimums and Maximums:

- | | |
|---------------------------------|---|
| Minimum width: 17" per section | Maximum width: 40" per venting section |
| Minimum height: 18" per section | Maximum height: 84" per venting section |

2 1/4" Sash Window - Minimums and Maximums:

- | | |
|---------------------------------|---|
| Minimum width: 20" per section | Maximum width: 40" per venting section |
| Minimum height: 18" per section | Maximum height: 84" per venting section |

Maximum: 23 square foot – (frame size) for double IG

Maximum: 19 square foot – (frame size) for triple IG

For more information, please visit our web site at www.lepagemillwork.com