

# CASEMENT WINDOWS

## WC11

Transom	20 1/2" (521) 16 1/2" (419) 12 1/2" (318)	20" (508) 16" (406) 12" (305)	13" (330) 9" (228) 5" (127)							
R.O. (mm)	17" (432)	19" (483)	21" (533)	25" (635)	29" (736)	33" (838)	37" (940)			
F.S. (mm)	16" (406)	18" (457)	20" (508)	24" (610)	28" (711)	32" (813)	36" (914)			
V.G. (mm)	9 1/8" (231)	11 1/8" (282)	13 1/8" (333)	17 1/8" (434)	21 1/8" (536)	25 1/8" (638)	29 1/8" (739)			
R.O.: Rough Opening										
F.S.: Frame Size										
V.G.: Visible Glass										
										* Meets Canadian EGRESS requirements
										** Meets U.S. EGRESS requirements
										*** Meets U.S. EGRESS requirements with Egress hinge

\* Please visit our web site for the energy performance of these products at [www.lepagemillwork.com](http://www.lepagemillwork.com)

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.

For masonry openings, please contact your local LePage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.

Venting configurations shown in units of the first line and first column are applicable to all units.

Units with 12" (305), 16" (406) and 20" (508) heights are shown stationary as standard transoms.

# CASEMENT WINDOWS

## WC21

Transom	WC21							
	20 1/2" (521) 16 1/2" (419) 12 1/2" (318)	20" (508) 16" (406) 12" (305)	13" (330) 9" (228) 5" (127)					
R.O. (mm)	31 3/4" (806)	35 3/4" (908)	39 3/4" (1010)	47 3/4" (1213)	55 3/4" (1416)	63 3/4" (1619)	71 3/4" (1822)	
F.S. (mm)	30 3/4" (780)	34 3/4" (882)	38 3/4" (984)	46 3/4" (1186)	54 3/4" (1390)	62 3/4" (1594)	70 3/4" (1796)	
V.G. (mm)	9 1/8" (231)	11 1/8" (282)	13 1/8" (333)	17 1/8" (434)	21 1/8" (536)	25 1/8" (638)	29 1/8" (739)	

R.O.: Rough Opening  
F.S.: Frame Size  
V.G.: Visible Glass

\* Meets Canadian EGRESS requirements

\*\* Meets U.S. EGRESS requirements

\*\*\* Meets U.S. EGRESS requirements with Egress hinge

\* Please visit our web site for the energy performance of these products at [www.lepagemillwork.com](http://www.lepagemillwork.com)

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.

For masonry openings, please contact your local LePage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.

Venting configurations shown in units of the first line and first column are applicable to all units.

Units with 12" (305), 16" (406) and 20" (508) heights are shown stationary as standard transoms.

# CASEMENT WINDOWS

## WC31

Transom	WC31					
	20 1/2" (521) 16 1/2" (419) 12 1/2" (318) 20" (508) 16" (406) 12" (305) 13" (330) 9" (228) 5" (127)					
R.O. (mm)	52 1/2" (1334)	58 1/2" (1486)	70 1/2" (1791)	82 1/2" (2096)	94 1/2" (2400)	106 1/2" (2705)
F.S. (mm)	51 1/2" (1307)	57 1/2" (1460)	69 1/2" (1763)	81 1/2" (2069)	93 1/2" (2372)	105 1/2" (2678)
V.G. (mm)	11 1/8" (282)	13 1/8" (333)	17 1/8" (434)	21 1/8" (536)	25 1/8" (638)	29 1/8" (739)
R.O. (mm)	62 1/2" (1588)	68 1/2" (1740)	80 1/2" (2045)	92 1/2" (2350)	104 1/2" (2655)	116 1/2" (2960)
F.S. (mm)	61 1/2" (1561)	67 1/2" (1713)	79 1/2" (2018)	91 1/2" (2323)	103 1/2" (2628)	115 1/2" (2933)
V.G. (mm)	11 1/8" (282)	13 1/8" (333)	17 1/8" (434)	21 1/8" (536)	25 1/8" (638)	29 1/8" (739)

R.O.: Rough Opening  
 F.S.: Frame Size  
 V.G.: Visible Glass

\* Meets Canadian EGRESS requirements

\*\* Meets U.S. EGRESS requirements

\*\*\* Meets U.S. EGRESS requirements with Egress hinge

\* Please visit our web site for the energy performance of these products at [www.lepagemillwork.com](http://www.lepagemillwork.com)

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options. For masonry openings, please contact your local Lepage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary. Venting configurations shown in units of the first line and first column are applicable to all units. Units with 12" (305), 16" (406) and 20" (508) heights are shown stationary as standard transoms.

# CASEMENT WINDOWS

## WC41

Transom	R.O. (mm)			
	20 1/2" (521) 16 1/2" (419) 12 1/2" (318)	77 1/4" (1962)	93 1/4" (2369)	109 1/4" (2775)
20" (508) 16" (406) 12" (305)	76 1/4" (1936)	92 1/4" (2340)	108 1/4" (2748)	124 1/4" (3156)
13" (330) 9" (228) 5" (127)	77 1/4" (1962)	93 1/4" (2369)	109 1/4" (2775)	125 1/4" (3181)
R.O. (mm)				
	77 1/4" (1962)	93 1/4" (2369)	109 1/4" (2775)	125 1/4" (3181)
F.S. (mm)				
	76 1/4" (1936)	92 1/4" (2340)	108 1/4" (2748)	124 1/4" (3156)
V.G. (mm)				
	13 5/8" (333)	17 5/8" (434)	21 1/8" (536)	25 5/8" (638)

24 1/2" (622)				
24" (610)				
28 1/2" (724)				
28" (711)				
32 1/2" (826)				
32" (813)				
36 1/2" (927)				
36" (914)				
39" (991)				
42 1/2" (1080)				
42" (1067)				
48 1/2" (1232)				
48" (1219)				
54 1/2" (1384)				
54" (1372)				
60 1/2" (1537)				
60" (1524)				
66 1/2" (1689)				
66" (1676)				
72 1/2" (1842)				
72" (1829)				
78 1/2" (1994)				
78" (1981)				

R.O.: Rough Opening  
F.S.: Frame Size  
V.G.: Visible Glass

\* Meets Canadian EGRESS requirements  
\*\* Meets U.S. EGRESS requirements  
\*\*\* Meets U.S. EGRESS requirements with Egress hinge

\* Please visit our web site for the energy performance of these products at [www.lepagemillwork.com](http://www.lepagemillwork.com)

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.

For masonry openings, please contact your local LePage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.

Venting configurations shown in units of the first line and first column are applicable to all units.

Units with 12" (305), 16" (406) and 20" (508) heights are shown stationary as standard transoms.

# CASEMENT WINDOWS

## WC51

Transom	WC51			
	20 1/2" (521) 16 1/2" (419) 12 1/2" (318) 20" (508) 16" (406) 12" (305) 13" (330) 9" (228) 5" (127)	 1206  1210  1214	 1406  1410  1414	 1806  1810  1814
R.O. (mm)	86" (2184)	96" (2438)	116" (2946)	136" (3454)
F.S. (mm)	85" (2157)	95" (2412)	115" (2917)	135" (3427)
V.G. (mm)	11 1/8" (282)	13 1/8" (333)	17 1/8" (434)	21 1/8" (536)
24 1/2" (622) 24" (610) 28 1/2" (724) 28" (711) 32 1/2" (826) 32" (813) 36 1/2" (927) 36" (914) 42 1/2" (1080) 42" (1067) 48 1/2" (1232) 48" (1219) 54 1/2" (1384) 54" (1372) 60 1/2" (1537) 60" (1524) 66 1/2" (1689) 66" (1676) 72 1/2" (1842) 72" (1829)	 1218  1222  1226  1230  1236  1242  1248  1254  1260  1266	 1418  1422  1426  1430  1436  1442  1448  1454  1460  1466	 1818  1822  1826  1830  1836  1842  1848  1854  1860  1866	 2218  2222  2226  2230*  2236*  2242**  2248**  2254**  2260**  2266**
R.O. (mm)	72 1/2" (1842)	82 1/2" (2094)	102 1/2" (2604)	122 1/2" (3114)
F.S. (mm)	72" (1829)	82" (2082)	102" (2592)	122" (3094)
V.G. (mm)	65" (1651)	85" (2157)	105" (2667)	125" (3174)

R.O.: Rough Opening  
 F.S.: Frame Size  
 V.G.: Visible Glass

\* Meets Canadian EGRESS requirements  
 \*\* Meets U.S. EGRESS requirements

\*\*\* Meets U.S. EGRESS requirements with Egress hinge

\* Please visit our web site for the energy performance of these products at [www.lepagemillwork.com](http://www.lepagemillwork.com)

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options. For masonry openings, please contact your local Lepage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary. Venting configurations shown in units of the first line and first column are applicable to all units. Units with 12" (305), 16" (406) and 20" (508) heights are shown stationary as standard transoms.

# CASEMENT WINDOWS

## WC2L

Transom	WC2L				
	20 1/2" (521) 16 1/2" (419) 12 1/2" (318) 20" (508) 16" (406) 12" (305) 13" (330) 9" (228) 5" (127)				
	1206	1406	1806	2206	2606
	1210	1410	1810	2210	2610
	1214	1414	1814	2214	2614
R.O. (mm)	47 3/4" (1213)	53 3/4" (1365)	65 3/4" (1670)	77 3/4" (1975)	89 3/4" (2280)
F.S. (mm)	46 3/4" (1187)	52 3/4" (1340)	64 3/4" (1645)	76 3/4" (1949)	88 3/4" (2254)
W.F. (mm)	18" (457)	20" (508)	24" (610)	28" (711)	32" (813)
V.G.F. (mm)	11 1/8" (282)	13 1/8" (333)	17 1/8" (434)	21 1/8" (536)	25 1/8" (638)
V.G.P. (mm)	23 1/8" (586)	27 1/8" (688)	35 1/8" (891)	43 1/8" (1094)	51 1/8" (1297)
	24 1/2" (622)	28 1/2" (724)	32 1/2" (826)	36 1/2" (927)	42 1/2" (1080)
	24" (610)	28" (711)	32" (813)	36" (914)	42" (1067)
	21" (533)	21" (533)	25" (635)	29" (736)	35" (889)
	17" (432)				
	1218	1418	1818	2218	2618
	1222	1422	1822	2222	2622
	1226	1426	1826	2226	2626*
	1230	1430	1830	2230*	2630*
	1236	1436	1836	2236*	2636**
	1242	1442	1842	2242**	2642**
	1248	1448	1848	2248**	2648**
	1254	1454	1854	2254**	2654**
	1260	1460	1860	2260**	2660**
	1266	1466	1866	2266**	2666**


































































R.O.: Rough Opening  
 F.S.: Frame Size  
 W.F.: Width of Flanker (comparable to the WC11 series)  
 V.G.: Visible Glass  
 V.G.F.: Visible Glass of Flanker  
 V.G.P.: Visible Glass of Picture Unit

\* Please visit our web site for the energy performance of these products at [www.lepagemillwork.com](http://www.lepagemillwork.com)  
 Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.  
 For masonry openings, please contact your local Lepage representative.  
 Lite patterns shown are 1/8" (22) SDL. Lite patterns for 3/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.  
 Venting configurations shown in units of the first line and first column are applicable to all units.  
 Units with 12" (305), 16" (406) and 20" (508) heights are shown stationary as standard transoms.  
 Some restrictions concerning SDL spacer bar availability may apply to glass surfaces larger than 30 sq. ft.

\* Meets Canadian EGRESS requirements  
 \*\* Meets U.S. EGRESS requirements  
 \*\*\* Meets U.S. EGRESS requirements with Egress hinge

# CASEMENT WINDOWS

## WC3L

Transom	R.O. (mm)				
	64 ½" (1638)	72 ½" (1842)	88 ½" (2248)	104 ½" (2654)	120 ½" (3061)
20 ½" (521) 16 ½" (419) 12 ½" (318)	 1206	 1406	 1806	 2206	 2606
20" (508) 16" (406) 12" (305)	 1210	 1410	 1810	 2210	 2610
13" (330) 9" (228) 5" (127)	 1214	 1414	 1814	 2214	 2614
F.S. (mm)					
	63 ½" (1613)	71 ½" (1816)	87 ½" (2223)	103 ½" (2629)	119 ½" (3035)
W.F. (mm)					
	18" (457)	20" (508)	24" (610)	28" (711)	32" (813)
V.G.F. (mm)					
	11 ⅞" (282)	13 ⅞" (333)	17 ⅞" (434)	21 ⅞" (536)	25 ⅞" (638)
V.G.P. (mm)					
	23 ⅞" (586)	27 ⅞" (688)	35 ⅞" (891)	43 ⅞" (1094)	51 ⅞" (1297)
	 1218	 1418	 1818	 2218	 2618
24 ½" (622)	 1222	 1422	 1822	 2222	 2622
28 ½" (724) 28 ⅞" (826) 28" (711)	 1226	 1426	 1826	 2226	 2626*
32" (813) 32" (813) 28" (711)	 1230	 1430	 1830	 2230*	 2630*
36 ½" (927) 36" (914) 36" (914)	 1236	 1436	 1836	 2236*	 2636**
42 ½" (1080) 42" (1067) 35" (889)	 1242	 1442	 1842	 2242***	 2642**
48 ½" (1232) 48" (1219) 41" (1041)	 1248	 1448	 1848	 2248***	 2648**
54 ½" (1384) 54" (1372) 47" (1194)	 1254	 1454	 1854	 2254***	 2654**
60 ½" (1537) 60" (1524) 53" (1346)	 1260	 1460	 1860	 2260***	 2660**
66 ½" (1689) 66" (1676) 59" (1498)	 1266	 1466	 1866	 2266***	 2666**

R.O.: Rough Opening  
 F.S.: Frame Size  
 W.F.: Width of Flanker (comparable to the WC11 series)  
 V.G.: Visible Glass  
 V.G.F.: Visible Glass of Flanker  
 V.G.P.: Visible Glass of Picture Unit

\* Please visit our web site for the energy performance of these products at [www.lepagemillwork.com](http://www.lepagemillwork.com)  
 Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.  
 For masonry openings, please contact your local Lepage representative.  
 Lite patterns shown are ⅞" (22) SDL. Lite patterns for ⅝" (16) SDL, 1 ¼" (31) SDL and other grilles may vary.  
 Venting configurations shown in units of the first line and first column are applicable to all units.  
 Units with 12" (305), 16" (406) and 20" (508) heights are shown stationary as standard transoms.  
 Some restrictions concerning SDL spacer bar availability may apply to glass surfaces larger than 30 sq. ft.

\* Meets Canadian EGRESS requirements  
 \*\* Meets U.S. EGRESS requirements  
 \*\*\* Meets U.S. EGRESS requirements with Egress hinge

# CASEMENT WINDOWS

## WC1P

Transom	20 1/2" (521)	16 1/2" (419)	12 1/2" (318)							
	20" (508)	16" (406)	12" (305)	2406	2806	3606	4406	5206		
	13" (330)	9" (228)	5" (127)	2410	2810	3610	4410	5210		
				2414	2814	3614	4414	5214		
R.O. (mm)	31" (787)	35" (889)	43" (1092)	51" (1295)	59" (1498)					
F.S. (mm)	30" (761)	34" (863)	42" (1066)	50" (1269)	58" (1472)					
V.G. (mm)	23 1/8" (586)	27 1/8" (687)	35 1/8" (891)	43 1/8" (1094)	51 1/8" (1297)					
R.O. (mm)	24 1/2" (622)	28 1/2" (724)	32 1/2" (826)	36 1/2" (927)	42 1/2" (1080)	48 1/2" (1232)	54 1/2" (1384)	60 1/2" (1537)	66 1/2" (1689)	72 1/2" (1842)
	24" (610)	28" (711)	32" (813)	36" (914)	42" (1067)	48" (1219)	54" (1372)	60" (1524)	66" (1676)	72" (1829)
F.S. (mm)	24" (610)	28" (711)	32" (813)	36" (914)	42" (1067)	48" (1219)	54" (1372)	60" (1524)	66" (1676)	72" (1829)
	24" (610)	28" (711)	32" (813)	36" (914)	42" (1067)	48" (1219)	54" (1372)	60" (1524)	66" (1676)	72" (1829)
V.G. (mm)	17" (432)	21" (533)	25" (635)	29" (736)	35" (889)	41" (1041)	47" (1194)	53" (1346)	59" (1498)	65" (1651)
	17" (432)	21" (533)	25" (635)	29" (736)	35" (889)	41" (1041)	47" (1194)	53" (1346)	59" (1498)	65" (1651)
	2418	2818	3618	4418	5218	2422	2822	3622	4422	5222
	2426	2826	3626	4426	5226	2430	2830	3630	4430	5230
	2436	2836	3636	4436	5236	2442	2842	3642	4442	5242
	2448	2848	3648	4448	5248	2454	2854	3654	4454	5254
	2460	2860	3660	4460	5260	2466	2866	3666	4466	5266

R.O.: Rough Opening  
 F.S.: Frame Size  
 V.G.: Visible Glass

\* Please visit our web site for the energy performance of these products at [www.lepagemillwork.com](http://www.lepagemillwork.com)

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.

For masonry openings, please contact your local LePage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.

All these units are shown stationary as standard transoms or picture units.

Some restrictions concerning SDL spacer bar availability may apply to glass surfaces larger than 30 sq.ft.