



Manu Data

Casement Window – Hybrid

Frame:

- Frame thickness 0.070" (1.8mm) PVC / 0.050" (1.3mm) Aluminium
- Frame depth 6 3/16" flush (Q-8395)

Sash:

- Thickness 0.070" (1.8mm) PVC / 0.063" (1.6mm) Aluminium

Exterior finish:

- Lepage paint (over 50 colors)

Operating Hardware:

- Truth: Encore series
- Retractable operator white
- Optional Egress

Weather-strip

- Soft PVC Co-extruded

Glass:

- Standard IG thickness 7/8" (22mm)
- Optional triple IG thickness 1 1/4" (32mm)
- Perimeter spacer: "Technoform". Standard colors bronze, white, black.
- Option: clear, Low-E argon, grey, bronze, pinhead, glue-chip and tempered 1 or 2 sides

Screen:

- Standard: charcoal fibreglass mesh
- Optional: invisible mesh, grey or black aluminium mesh
- Standard: white surround

Grilles:

- Internal georgian 3/4", 1" or 1 3/4"
- Internal flat 5/16", 5/8", 3/4" or 1"
- Internal tubular: white, brass or pewter

Simulated Divided Lites (SDL):

- 7/8", 1 1/4" or 2" SDL PVC
- Optional for white, bronze or black spacer bars.

Interior Jamb Extension:

- Natural or PVC clad
- Entirely made of PVC 4" (Quad-8038), 5 3/4" (Q-7705), 5 3/4" (Q-8322 whit interior casing Q-8321) or 7" (V-238-240)

Brickmould options:

- Extruded aluminum 908 Brickmould (D-065)
- Extruded aluminum 2 3/4" Flat casing (D-066)
- Extruded aluminum 3 1/2" Flat casing (D-050)
- Extruded aluminium 3 15/16" Backbend (D-090)
- Nailing fin

Sill Extension:

- Standard D-082
- Optional historic D-083

Minimums and Maximums:

Minimum width:	13"	(opening 60°)	17" (opening 90°)
Minimum height:	13"		
Maximum width:	40"		
Maximum height:	84"		
Maximum frame size:	19 square feet		

For more information, please visit our web site at www.lepagemillwork.com