



Manu Data

Casement Window – PVC

Frame:

- Frame thickness 0.070" (1.8mm)
- Frame depth 4 ½" flush (Q-8300), or 6" flush (Q-8395) or 3 ¼" with brickmould (Q-8320) or 4 ½" with brickmould (Q-8305) or 4 ½" with brickmould (Q-8369) (renovation)

Sash:

- Thickness 0.070" (1.8mm)

Exterior finish:

- Lepage paint (over 50 colors)

Operating Hardware:

- Truth: Encore series
- Retractable operator white
- Optional Egress

Weather-strip

- Soft PVC Co-extruded

Glass:

- Standard IG thickness ⅞" (22mm)
- Optional triple IG thickness 1 ¼" (32mm)
- Perimeter spacer: "Technoform". Standard colors bronze, white, black.
- Option: clear, Low-E argon, grey, bronze, pinhead, glue-chip and tempered 1 or 2 sides

Screen:

- Standard: charcoal fibreglass mesh
- Optional: invisible mesh, grey or black aluminium mesh
- Standard: white surround

Grilles:

- Internal georgian ¾", 1" or 1 ¾"
- Internal flat 5/16", 5/8", ¾" or 1"
- Internal tubular: white, brass or pewter

Simulated Divided Lites (SDL):

- ⅞", 1 ¼" or 2" SDL PVC
- Optional for white, bronze or black spacer bars.

Interior Jamb Extension:

- Natural or PVC clad
- Entirely made of PVC 4" (Quad-8038), 5 ¾" (Q-7705), 5 ¾" (Q-8322 with interior casing Q-8321) ou 7" (V-238-240)

Brickmould options:

- PVC brickmould 7/8" (Q-8375), 1 1/8" (Q-8439), 1 3/8" (Q-8307), 2" (Q-8333), 4" (Q-8338)
- Groove cover (Q-8206)
- Nailing fin (D-068 & D-160)
- Exterior extension flush (Q-8332)
- Interior hiding groove (Q-8309)
- Interior casing (Q-8321)

Minimums and Maximums:

Minimum width:	13"	(opening 60°)	17" (opening 90°)
Minimum height:	13"		
Maximum width:	40"		
Maximum height:	84"		
Maximum frame size:	19 square feet		

For more information, please visit our web site at www.lepagemillwork.com